



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. RATING: 2A @125VAC, 1A @250VAC
 5. CONTACT RESISTANCE: 10mILLI-OHMS max.
 6. DIELECTRIC STRENGTH: 1000 VAC-1Minute
 7. INSULATION RESISTANCE: 200Mega OHMS min.
 8. MATERIALS:

HOUSING: ZINC ALLOY DIE CAST, SATINE CHROME PLATING
 CYLINDER: ZINC ALLOY W/SATIN CHROME PLATING
 TERMINAL AND CONTACTS: SILVER PLATED
 KEYS (2) KEY CODE 10001:
 TUBULAR STEEL, NICKLE PLATING

LEGEND
 ○ =OFF POSITION
 ■ =INDICATES KEY PULL
 ✕ =INDICATES NO KEY PULL

RECOMMENDED PANEL CUTOUT

| | | | | |
|------|---------|-------------------------|----------|------|
| REV. | ECN No. | DESCRIPTION | DATE | CHKD |
| A | 11737 | RELEASED FOR PRODUCTION | 10/12/01 | CJB |

| | | | | | | | |
|--------------|--|-------|--|----------|-----|---------|-----|
| TITLE | | SCALE | | DATE | DR | DWG | REV |
| K0124D-10001 | | 1.5:1 | | 10/12/01 | CJB | K500106 | A |



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED